

2026

ottobock.

Bathing support *Robby*.

☐ Quotation

☐ **Order**

Billing Address

PO no.

Customer Name

Street

County PC

Shipping address (if different from billing address)

Customer Name

Street

County PC

Name Date Signature



Base Price -

Please email all orders to
Bockuk@ottobock.com

Valid from 01.03.2026 to 31.12.26
Please ensure you are using the latest order form
v2

By placing the order, you agree to comply with the instructions for use/service manuals for accessories and products of other manufacturers when combining them with an Ottobock product, in addition to the instructions for use/service manuals of the respective Ottobock products. Also you confirm to have read, understood and accepted, our general terms and conditions. In addition, you agree, upon placing an order, to conduct your own conformity assessment or approval in accordance with national requirements if and when you implement modifications or attachments that do not meet the specifications of Ottobock instructions for use/service manuals.
Wheelchairs with CLT package cannot be returned or exchanged

Standard equipment Selection (unless alternative selected)

- Folding bathing and lying support that can be adapted to grow with the user
- Net upholstery (blue), washable
- Lap belt and leg strap
- Frame colour: silver

The number codes contained in this order form are not intended to be used as article numbers for spare parts orders.
Please scan the QR code to access the spare parts catalogue for any spare parts orders.



Bathing support *Robby*.

Bathing support Robby

☐	HR51040000-027	Robby size 1	£986.00
☐	HR51050000-027	Robby size 2	£1076.00

Accessories

☐	HR51045300	Trunk belt	£61.00
☐	HR51045200-103	Adjustable head support pads (can also used as trunk support pads)	£159.00

Information



**Adjustable head
support pads**

Technical data

	Size 1	Size 2
Seat depth (depending on strap tension and expansion of telescopic tubes)	200 – 240 mm	310 – 425 mm
Back support length incl. head section	630 – 725 mm	890 – 940 mm
Overall width	360 mm	380 mm
Overall length (support surface)	1150 – 1330 mm	1470 – 1730 mm
Max. load capacity	30 kg	60 kg
Weight	3.8 kg	4.3 kg