

2022/23

ottobock.

Base Price -

Order no.:

Valid from 01.04.22 to 31.03.23
Please ensure you are using the latest order form

☐ Provide estimate only☐ Order

Billing address/customer number

Delivery address

Sales person

Name

Date Signature

By placing the order, you agree to comply with the instructions for use/service manuals for accessories and products of other manufacturers when combining them with an Ottobock product, in addition to the instructions for use/service manuals of the respective Ottobock products. Also you confirm to have read, understood and accepted, our general terms and conditions. In addition, you agree, upon placing an order, to conduct your own conformity assessment or approval in accordance with national requirements if and when you implement modifications or attachments that do not meet the specifications of Ottobock instructions for use/service manuals.

Robby

Bathing support



Standard equipment

- Folding bathing and lying support that can be adapted to grow with the user
- Net upholstery (blue)
- Lap belt and leg strap
- Frame colour: silver

Robby bathing support

HR51040000-027	<input type="checkbox"/>	Robby, size 1 (seat depth 20 – 24 cm, back support height incl. head section 63 – 72.5 cm) Bathing and lying support, includes washable net upholstery, lap belt, leg straps; max. load capacity 30 kg	£810.00
HR51050000-027	<input type="checkbox"/>	Robby, size 2 (seat depth 31 – 42.5 cm, back support height incl. head section 89 – 94 cm) Bathing and lying support, includes washable net upholstery, lap belt, leg straps; max. load capacity 60 kg	£883.00

Accessories

HR51045300	<input type="checkbox"/>	Trunk belt	£49.00
HR51045200-103	<input type="checkbox"/>	Adjustable head support pads (can also be used as trunk support pads)	£103.00

Information



Adjustable head support pads

Technical Data

	Size 1	Size 2
Seat depth (depending on strap tension and expansion of telescoping tubes)	200 – 240 mm	310 – 425 mm
Back support height	630 – 725 mm	890 – 940 mm
Overall width	360 mm	380 mm
Overall length (support surface)	1150 – 1330 mm	1470 – 1730 mm
Max. load capacity	30 kg	60 kg
Weight	3.8 kg	4.3 kg